



**KARNATAKA ANTIBIOTICS &
PHARMACEUTICALS LIMITED**

(A Government of India Enterprise)

ENQUIRY REF No:	KAPL/CNW/014/0551
DATE	07-07-2025
DUE DATE	10-07-2025 (13.00HRS)

Dear Sir,

Please submit your lowest and competitive offer in a SEALED ENVELOPE, DULY SUPERSCRIBING OUR ABOVE ENQUIRY REF. NO., DATE and DUE DATE on it/ OR MAIL, with other details of F.O.R terms, Taxes, Credit period, Delivery offered, Name of the Make, Detailed Specification etc., for below mentioned material/s

SL NO.	ITEM CODE	ITEM DESCRIPTION	UOM	QTY
01	ICMNWS02	POE NETWORK SWITCH GIGA BIT- 5-PORT	NOS	2

- 1) Please ensure that your offer reaches us on or before Due Date by courier OR speed post Or you can also mail us to our email: puren@kaplindia.com
- 2) Please send your quotation mentioning item code

OTHER TERMS:

- | | |
|---------------------------------|---------------------------|
| 1. F.O.R TERMS | : DOOR DELIVERY TO PEENYA |
| 2. GST % | : PLEASE SPECIFY |
| 3. PACKING & FORWARDING CHARGES | : NOT APPLICABLE |
| 4. CREDIT PERIOD | : 30 DAYS |
| 5. DELIVERY OFFERED | : PLEASE SPECIFY |
| 6. ATTACHED PAGES | : 1 PAGES |

NOTE: IN CASE YOU ARE NOT QUOTING PLEASE SEND THE REGRET LETTER.

Thanking you,

Yours faithfully,
For KARNATAKA ANTIBIOTICS
& PHARMACEUTICALS LIMITED


YUVARAJA M
DEPUTY MANAGER PURCHASE DEPT
MOB: 9945317873

Technical Specifications

General

Interfaces	• 5 x 10/100/1000BASE-T ports
Standards	• IEEE 802.3 10BASE-T Ethernet (twisted-pair copper) • IEEE 802.3u 100BASE-TX Fast Ethernet (twisted-pair copper) • IEEE 802.3ab 1000BASE-T Gigabit Ethernet • IEEE 802.3x flow control • IEEE 802.1p QoS • ANSI/IEEE 802.3 NWay auto-negotiation
Media Interface Exchange	• Auto MDI/MDI-X adjustment on all ports

Performance

Switching Fabric	• 10 Gbps
Transmission Method	• Store-and-forward
Data Transfer Rates	• Gigabit Ethernet • 2000 Mbps (full-duplex) • Fast Ethernet • 100 Mbps (half-duplex), 200 Mbps (full-duplex) • Ethernet • 10 Mbps (half-duplex), 20 Mbps (full-duplex)
Packet Filtering / Forwarding Rates	• 7.44 Mpps
MAC Address Table	• 2K entries per device
RAM Buffer	• 64 KB per device

PoE

PoE Standards	• IEEE 802.3af	• IEEE 802.3at
PoE-Capable Ports	• Ports 1 to 4	
Power Budget	• 60 W (30 W max. per PoE port)	

Physical

LEDs	• Power / PoE Max (per unit), Power / Status (per port), Activity / Link and Speed (per port)
Weight	• 0.26 kg (9.17 oz)
Dimensions	• 100 x 98 x 28 mm (3.94 x 3.86 x 1.10 in)
DC Input	• External 53.5 V / 1.2 A power adapter
Power Consumption	• 64.5 W maximum (PoE on) • 3.08 W maximum (PoE off) • 0.54 W (standby)
Temperature	• Operating: 0 to 40 °C (32 to 104 °F) • Storage: -10 to 70 °C (-40 to 158 °F)
Humidity	• Operating: 0% to 95% RH non-condensing • Storage: 0% to 95% RH non-condensing

Certifications

Safety	• cUL, CB, LVD, BSMI
EMI/EMC	• CE, BSMI, FCC, VCCI, RCM